



A Series 500 550 600

The ideal family boat for every occasion

Standard Features

Hypatex 2-tone blue and light grey tubes, with 6 grab handles, moulded lifeline holders, lifelines, wear patches, dual rubbing strake

Bow fairlead on GRP moulding with stainless steel cleat

Deep V hull, monocoque construction with moulded deck

Splashwell including drains, hull drains

Integral sculpted rear seat with large storage area

Bow eye, 2 transom U bolts, anchor eye

90 litres underdeck fuel tank (500, 550, 600)

Bow seat with cushion and locker beneath

Odyssey console with front seat and storage (500, 550, 600)

2 x 2-man jockey seats (600)

2 x 1-man jockey seats (500, 550)

Steering wheel, helm

Owner's manual

Accessories

Odyssey console without front seat

Teak decking

1-man jockey seat - all models

Backrests for sculpted rear seat

Swing back helm seat

Bimini cover


Mooring cover

Boarding platform with telescopic ladder


A-frame with navigation lights

Hydraulic steering

500



550



600



| Technical Specifications | 500 | 550 | 600 |
|-----------------------------|--------|--------|--------|
| Overall Length | 5.00m | 5.50m | 6.00m |
| Internal Length | 4.05m | 4.55m | 5.05m |
| Overall Width | 2.28m | 2.28m | 2.28m |
| Inside Width | 1.38m | 1.38m | 1.38m |
| Tube Diameter | 0.46m | 0.46m | 0.46m |
| Number of Air Chambers | 5 | 5 | 5 |
| Number of Persons | 8 | 10 | 12 |
| Maximum Payload | 765kg | 1000kg | 1100kg |
| Boat Weight Std Spec | 410kg | 450kg | 520kg |
| Maximum Power | 80hp | 100hp | 120hp |
| Engine Shaft | L | L | L |
| Design Category | C | B | B |
| Boat Weight inc Eng/Rigging | 750kg | 793kg | 890kg |
| Boat & Trailer Weight | 1150kg | 1193kg | 1290kg |
| Trailer Weight | 400kg | 400kg | 400kg |
| Height on Trailer | 2.35m | 2.35m | 2.35m |
| Height of Boat | 1.80m | 1.80m | 1.80m |
| Engine Weight | 170kg | 170kg | 200kg |
| Prop Size | 19" | 19" | 19" |
| Draft in Water at Rest | 0.47m | 0.47m | 0.47m |
| Max Speed | 32knts | 35knts | 40knts |

Ribeye carries out a continuous program of product improvement and safety awareness. Specifications are subject to change without notice, although all details are correct at the time of going to press. Ribeye products may be produced with a different trim level than originally specified. All dimensions are +/- 3%.

Please note that performance of your boat depends on engine size, propeller selection, trim settings, payload distribution and operating conditions. Refer to sections within this manual and within your engine owner's manual to obtain the best performance from your Ribeye.

Falmouth Ribeye, Falmouth Marina, Falmouth, Cornwall, TR11 2TD
Tel: 01326 211800 · www.falmouthribeye.co.uk · Email: sales@falmouthribeye.co.uk



A Series 500 550 600

The ideal family boat for every occasion

Standard Features

Hypatex 2-tone blue and light grey tubes, with 6 grab handles, moulded lifeline holders, lifelines, wear patches, dual rubbing strake

Bow fairlead on GRP moulding with stainless steel cleat

Deep V hull, monocoque construction with moulded deck

Splashwell including drains, hull drains

Integral sculpted rear seat with large storage area

Bow eye, 2 transom U bolts, anchor eye

90 litres underdeck fuel tank (500, 550, 600)

Bow seat with cushion and locker beneath

Odyssey console with front seat and storage (500, 550, 600)

2 x 2-man jockey seats (600)

2 x 1-man jockey seats (500, 550)

Steering wheel, helm

Owner's manual

Accessories

Odyssey console without front seat

Teak decking

1-man jockey seat - all models

Backrests for sculpted rear seat

Swing back helm seat

Bimini cover


Mooring cover

Boarding platform with telescopic ladder

A-frame with navigation lights

Hydraulic steering

500



550



600



| Technical Specifications | 500 | 550 | 600 |
|-----------------------------|--------|--------|--------|
| Overall Length | 5.00m | 5.50m | 6.00m |
| Internal Length | 4.05m | 4.55m | 5.05m |
| Overall Width | 2.28m | 2.28m | 2.28m |
| Inside Width | 1.38m | 1.38m | 1.38m |
| Tube Diameter | 0.46m | 0.46m | 0.46m |
| Number of Air Chambers | 5 | 5 | 5 |
| Number of Persons | 8 | 10 | 12 |
| Maximum Payload | 765kg | 1000kg | 1100kg |
| Boat Weight Std Spec | 410kg | 450kg | 520kg |
| Maximum Power | 80hp | 100hp | 120hp |
| Engine Shaft | L | L | L |
| Design Category | C | B | B |
| Boat Weight inc Eng/Rigging | 750kg | 793kg | 890kg |
| Boat & Trailer Weight | 1150kg | 1193kg | 1290kg |
| Trailer Weight | 400kg | 400kg | 400kg |
| Height on Trailer | 2.35m | 2.35m | 2.35m |
| Height of Boat | 1.80m | 1.80m | 1.80m |
| Engine Weight | 170kg | 170kg | 200kg |
| Prop Size | 19" | 19" | 19" |
| Draft in Water at Rest | 0.47m | 0.47m | 0.47m |
| Max Speed | 32knts | 35knts | 40knts |

Ribeye carries out a continuous program of product improvement and safety awareness. Specifications are subject to change without notice, although all details are correct at the time of going to press. Ribeye products may be produced with a different trim level than originally specified. All dimensions are +/- 3%.

Please note that performance of your boat depends on engine size, propeller selection, trim settings, payload distribution and operating conditions. Refer to sections within this manual and within your engine owner's manual to obtain the best performance from your Ribeye.

Falmouth Ribeye, Falmouth Marina, Falmouth, Cornwall, TR11 2TD
Tel: 01326 211800 · www.falmouthribeye.co.uk · Email: sales@falmouthribeye.co.uk

Powered by  **YAMAHA**

